

ITEM	TLF3-700	TLF3-800	TLF3-900	TLF3-1000	TLF3-1100
Width of Material (mm)	75 ~ 700	75 ~ 800	75 ~ 900	75 ~ 1000	75 ~ 1100
Thickness of Material (mm)	0.5 ~ 3.2				
Max. Coil Weight (kg)	5000 ( 7000 , 10000* )				
Coil I.D. (mm)	508				
Max. Coil O.D. (mm)	1500				
Max. Speed (m/min)	16				
Feed Pitch Accuracy (mm)	±0.15(Within 500mm feed length)				
Feed Roll	Upper 1 / Lower 1				

ITEM	TLF3-700	TLF3-800	TLF3-900	TLF3-1000	TLF3-1100
Work Roll	upper 4 / lower 3				
Backup Roll	Provided				
Power Supply	220VAC 60HZ				
Air Supply	5 kg/cm <sup>2</sup>				
Uncoiler Expansion	Hydraulic				
Main Motor (kw)	5.0 kW	7.0 kW			
Uncoil Motor (HP)	5.0 HP (7.0 HP, 10 HP*) + Inverter				
Feed Level (mm)	Customer request ±100				

ITEM	TLF3-1200	TLF3-1300	TLF3-1400	TLF3-1500	TLF3-1600
Width of Material (mm)	75 ~ 1200	75 ~ 1300	75 ~ 1400	75 ~ 1500	75 ~ 1600
Thickness of Material (mm)	0.5 ~ 3.2				
Max. Coil Weight (kg)	5000 (7000 , 10000* )				
Coil I.D. (mm)	508				
Max. Coil O.D. (mm)	1500				
Max. Speed (m/min)	16				
Feed Pitch Accuracy (mm)	±0.15(Within 500mm feed length)				
Feed Roll	Upper 1 / Lower 1				
Work Roll	upper 4 / lower 3				
Backup Roll	Provided				

ITEM	TLF3-1200	TLF3-1300	TLF3-1400	TLF3-1500	TLF3-1600
Power Supply	220VAC 60HZ				
Air Supply	5 kg/cm <sup>2</sup>				
Uncoiler Expansion	Hydraulic				
Main Motor (kw)	7.0 kW		11.0 kW		
Uncoil Motor (HP)	5.0 HP (7.0 HP, 10 HP*) + Inverter				
Feed Level (mm)	Customer request ±100				